

# Gibson Dual-Chamber Spinner Hangers

- Speed batch blasting of sensitive parts
- Deliver 360° workpiece coverage
- Continue working during loading

**Two Blast Chambers** index from front to back so an operator can load and unload parts in one chamber while high-efficiency blast wheels clean,peen or prep parts on the other side in the second chamber.

**Motor-Driven Shaft** spins workpiece fixtures for even, 360° exposure of part surfaces.

**Cast Liners** on chamber walls extend equipment life.

**PLC Programming** assures precise coordination between automated functions.



Gibson Spinner Hangers provide an ideal solution for batch blasting many types of parts too fragile or awkward for other methods of automated finishing. These systems play a profit-boosting role across a broad range of metal-intensive industries by improving quality and efficiency during the cleaning, peening, prepping and finishing of almost any workpiece suitable for mounting on hooks.

Our systems include two work chambers mounted on an indexing turntable. As the turntable steps through programmed positions, one chamber exposes parts to a contained blast stream emanating from high-efficiency wheels while the other opens to the operator, who loads and unloads parts from the un-contained chamber. To assure uniform coverage, a spindle rotates the hangers within the working chamber's blast envelope.

Like all Gibson systems, our Spinner Hangers are easy to operate and install. Plus, they deliver consistent results whether working intermittently or non-stop in a multi-shift production facility.

PLC programming assures repeatable performance cycle after cycle, and cast liners on work-chamber walls extend equipment life. Hanger capacities from 125 to 2,000 pounds fit most applications.

For additional information about our line of Spinner Hanger Blasters, refer to the next page, contact Gibson and visit our web site at [www.gibson-parts.com](http://www.gibson-parts.com) where you can see videos of our Spinner Hangers in action.

## Dual-Chamber Spinner Hanger System Specifications

MODEL	12x24 SH	12x44 SH	24x48 SH	24x60 SH	36x72 SH
<b>Capacities</b>					
Hook load	125 lb	250 lb	1,500 lb	1,500 lb	2,000 lb
Maximum blast envelope	12" dia x 16"	12" dia x 36"	24" dia x 36"	24" dia x 48"	36" dia x 60"
Optimal blast envelope	12" dia x 12"	12" dia x 24"	24" dia x 24"	24" dia x 36"	36" dia x 48"
Media charge (Steel)	200 lb	300 lb	2,000 lb	2,000 lb	4,000 lb
<b>Blast chambers</b>					
	Two	Two	Two	Two	Two
<b>Direct-drive blast wheels</b>					
	One, 5 hp	Two, 5 hp	Two, 7.5 hp	Two, 7.5 hp	Two, 10 hp
<b>Dimensions (HxWxD, inches)</b>					
Spinner hanger, cabinet only	85x47x50	133x47x50	149x96x79	160x96x79	216x134x117
Dust collector	83x40x26	83x40x26	127x50x36	127x50x36	173x52x64
<b>Requirements</b>					
Ventilation	500 cfm	800 cfm	2,000 cfm	2,000 cfm	3,000 cfm
<b>Electrical (460/60/3)</b>					
Spinner Hanger only	9.4 amp	15.4 amp	23.3 amp	23.3 amp	30.0 amp
With dust collector	10.2 amp	18.2 amp	29.5 amp	29.5 amp	38.9 amp
<b>Standard Features</b>					
Cast liners on chamber walls		√	√	√	√
Multiple indexing	√	√	√	√	√
PLC programmed		√	√	√	√
Safety bump bar strip	√	√	√	√	√
<b>Factory Options:</b> Variable frequency drive for blast wheels • Rotary scalping screen • Safety light curtain • Abrasion-resistant liners & packages					

## Other Gibson Spinner Hangers



High-capacity blast machine performs both **Table** and **Spinner Hanger** operations, providing the versatility to meet various customer needs.



**Y-track** branches into two rails so one fixture can be loaded and unloaded while parts on the second fixture undergo blasting.



**Pneumatic Trolley** transports heavy loads of parts in and out of the blast enclosure.



INTERNATIONAL SURFACE PREPARATION CANADA LTD

5125 Timberlea Blvd Mississauga Ont

866-669-6643      sales@ispcltd.com